

In the Claims:

Please amend the claims as follows:

1. (Once Amended) An apparatus for determining a blood flow in a vessel, comprising:

(a) an elongate catheter having a stenosis reducing member [an angioplasty balloon], a blood property change port and a downstream sensor spaced from the port for producing a signal corresponding to a blood property.

2. (Once Amended) The apparatus of Claim 1, wherein one of the sensor and the catheter [are] is configured to locate the sensor with respect to the vessel to minimize wall effects.

10. (Once Amended) The catheter of Claim 9, wherein one of the sensor and the catheter [are] is configured to locate the sensor with respect to the vessel to minimize wall effects.

15. (Once Amended) An apparatus for determining blood flow, comprising:

(a) a dilution indicator source;

(b) a[n angioplasty] catheter connectable to the dilution indicator source, the [angioplasty] catheter having means for performing a vascular corrective procedure [an angioplasty balloon], a dilution indicator port for passing a dilution indicator therethrough and a downstream sensor for producing a signal corresponding to passage of the dilution indicator; and

(c) a controller connected to the dilution indicator source and the sensor for calculating a blood flow in response to the signal from the sensor.

16. (Once Amended) A method for quantitatively measuring [an angioplasty] a reduced stenosis induced flow change, comprising:

(a) inserting a catheter and a blood property sensor into a vessel having a blood flow corresponding to the stenosis [angioplasty];

(b) introducing a first change in a blood property upstream of the blood property sensor;

(c) detecting passage of the first change in the blood property at the blood property sensor;

(d) reducing the stenosis of in the vessel [expanding an angioplasty member];

(e) introducing a second change in the blood property upstream of the sensor;

(f) detecting passage of the second change in the blood property at the blood property sensor; and

(g) determining a change in blood flow corresponding to the detected passage of the first change in the blood property and the second change in the blood property.

sub
D4

17. (Once Amended) The method of Claim 16, wherein inserting a catheter and a blood property sensor into a vessel [having a blood flow corresponding to the angioplasty] includes inserting a first catheter having a stenosis reducing [the angioplasty] member and a second catheter having the blood property sensor.

18. (Once Amended) The method of Claim 16, wherein inserting a catheter and a blood property sensor into a vessel [having a blood flow corresponding to the angioplasty] includes inserting a catheter having a stenosis reducing [the angioplasty] member and the blood property sensor.

Sub BB
19. (Once Amended) A method of monitoring blood flow during a vascular corrective procedure [angioplasty], comprising:

- A3
- (a) inserting a[n angioplasty] catheter into a vessel;
 - (b) employing the catheter to perform a vascular correction in the vessel [expanding the angioplasty catheter];
 - (c) introducing a first blood property change;
 - (d) detecting passage of the first blood property change past a downstream sensor on the catheter; and
 - (e) calculating the blood flow in response to the change in blood property and passage of the blood property past the downstream sensor.

20. (Once Amended) An apparatus for determining [a] blood flow in a vascular passage, comprising:

- (a) a catheter having means for increasing the effective size of a portion of the vascular passage, the catheter including a dilution indicator introduction port and a downstream blood property sensor; and
- (b) a controller operably connected to the blood property sensor for calculating a flow through the vascular passage corresponding to a signal from the blood property sensor.